



Product description

A ready-to-use, solvent-free, transparent adhesive for carpet tiles, enriched with acrylic dispersion and featuring a liquid consistency, specifically formulated for roller application. It creates a thin, transparent layer that effectively prevents carpet tiles from slipping and shifting.



Application Areas

Indoors, it is suitable for application on all absorbent and non-absorbent surfaces, including leveled screed, concrete, metal, plywood, betopan, linoleum, PVC, and tiles.



Technical specifications

Intensity	1.05±0.05 g/cm ³
Wait time	30-60 minutes
Hair removal duration	5-10 minutes
Working hours	15-20 minutes
Commencement time of movement	24 hours
Total drying duration.	72 hours

The information presented in this technical data sheet is derived from data collected during testing. The user assumes full responsibility for the proper use of our original product. Our company is exclusively accountable for the product's quality. This data sheet supersedes the information found in the prior data sheet. Our company retains the right to modify any information included in this data sheet.



Advantages

- It inhibits the movement of carpet tiles and prevents the formation of gaps between them.
- Dries rapidly,
- Suitable for floors exposed to substantial loads from wheels and equipped with a heating system.
- It is applicable when installing antistatic carpet tiles.
- It is applicable to both absorbent and impermeable surfaces.
- Glued carpet tiles can be effortlessly removed.
- A conductive floor can be created on it.
- It is free of solvents, water-based, and environmentally sustainable.
- The product is prepared for use and simple to apply.



Preparing the foundation

The surface designated for painting must be devoid of oil and dirt, level, and absorbent. It must also possess pressure resistance. Any loose areas should be cleaned and repaired with Quattro QuaFIX 5001 at least 24 hours prior to the application of AF-4302. Uneven floors must be leveled using Quattro SLF self-leveling screed.



Mixture

AF-4302 is prepared for immediate use; there is no requirement to incorporate external substances.



About the Application

Thoroughly shake the mixing container, then transfer the product into a clean container and apply a thin, even layer to the floor using a fine-mesh roller. Exercise caution to prevent puddling. Allow the adhesive to become clear (approximately 30-60 minutes) before installing the carpet tiles. Remove any adhesive residue from the edges with warm water before it dries.

AF-4302

Acrylic-based adhesive for carpet tiles.



Consumption

50-150 g/m²



PACKAGE

20 kg plastic container



Shelf life

In unopened packaging, it can be stored for 12 months in a cool, dry location shielded from sunlight at a temperature ranging from +10°C to +25°C.



Attention

Avoid application in environments where ambient temperatures fall below 5°C or exceed 30°C. Refrain from applying in direct sunlight, rain, or windy conditions. Do not apply to surfaces that have been subjected to prolonged sunlight exposure, nor to frozen surfaces or those at risk of freezing within 24 hours.

R10: Keep away from children.

R20/22: Harmful if inhaled or ingested.

R52/53: Toxic to aquatic life, may result in long-term detrimental effects in the aquatic ecosystem.

R65: Harmful. May result in lung damage if ingested.

S7: Store in a tightly sealed container.

S24/25: Avoid contact with eyes and skin. S28: In the event of skin contact, rinse immediately with abundant water.

S29: Do not discharge into drains.

S46: If ingested, seek medical attention promptly and present this container or label.