



## Product description

This is a high-performance, solvent-based acrylic polish that is UV-stable, dust-resistant, and designed to enhance low-adhesion surfaces with a clear, high-gloss finish.



## Application Areas

- Swimming pools, pedestrian pathways, plazas,
- On pedestrian pathways, sidewalks, subterranean crossings,
- Residential complexes, retail centers, service stations,
- To safeguard and enhance cement-based surfaces,
- To prolong the lifespan of concrete,
- On surfaces that necessitate a glossy finish,
- To prevent the accumulation of dust on surfaces,
- For concrete surfaces to achieve a luminous, transparent, and vibrant appearance,
- At manufacturing facilities,
- In parking facilities and storage areas,
- On surfaces where the hardener has been applied,
- It is utilized for covering surfaces such as concrete and screed.



## Technical specifications

Intensity	0.88±0.03 kg/l
Viability	2 seconds
LOS	742 g/l
Total drying duration.	5 days

The information presented in this technical data sheet is derived from data collected during testing. The user assumes full responsibility for the proper use of our original product. Our company is exclusively accountable for the product's quality. This data sheet supersedes the information found in the prior data sheet. Our company retains the right to modify any information included in this data sheet.



## Advantages

- Simple to apply, as it comprises a single component.
- It offers substantial resistance to chlorine (salt) and gaseous influences.
- Due to the rapid evaporation of the solvent, it dries swiftly.
- By enhancing water resistance, it inhibits the freezing of concrete.
- prevents the potential occurrence of cracks.
- Offers protection against ultraviolet radiation.
- Resistant to alkaline compounds.
- Fills non-structural fissures in hair.
- This results in vibrant colors without forming a pattern on the concrete.



## Preparing the foundation

The surface must be devoid of any substances that may hinder adhesion, such as dust, dirt, oil, and loose particles. It is advisable to clean the surface with a damp cloth and ensure it is dry prior to application. When dealing with wet surfaces, perform an adhesion test by applying a small sample of adhesive to a limited area.



## Mixture

CP-2602 is a single-component, ready-to-use formulation. It must be mixed thoroughly prior to application. Dilution is not allowed. It can be applied manually or with automatic sprayers, a brush, or a short-nap roller.



## Consumption

Brush, roller (application): 0.10 – 0.20 L (per 1 m<sup>2</sup> of surface) Spray (impregnation): 0.15 – 0.25 L (per 1 m<sup>2</sup> of surface)



## PACKAGE

17-liter capacity



## Shelf life

In unopened packaging, it can be stored for 12 months in a cool, dry location shielded from sunlight at a temperature ranging from +10°C to +25°C.



## Attention

Avoid application in environments where ambient temperatures fall below 5°C or exceed 30°C. Refrain from applying in direct sunlight, rain, or windy conditions. Do not apply to surfaces that have been subjected to prolonged sunlight exposure, nor to frozen surfaces or those at risk of freezing within 24 hours.

R10: Keep away from children.

R20/22: Harmful if inhaled or ingested.

R52/53: Toxic to aquatic life, may result in long-term detrimental effects in the aquatic ecosystem.

R65: Harmful. May result in lung damage if ingested.

S7: Store in a tightly sealed container.

S24/25: Avoid contact with eyes and skin. S28: In the event of skin contact, rinse immediately with abundant water.

S29: Do not discharge into drains.

S46: If ingested, seek medical attention promptly and present this container or label.