



Product description

It is a modified chlorinated rubber alkyd resin, an air-drying paint that penetrates surfaces effectively, dries rapidly, and exhibits high abrasion resistance.



Application Areas

- Road markings applicable to asphalt and concrete surfaces.
- The paint was designed for marking lines on highways, at airports, on sidewalks, pedestrian crossings, and various other surfaces.



Technical specifications

Touch drying time	10-15 minutes
Thorough drying	3.5-4 hours
Interlevel waiting period	A minimum of three hours
Coverage capacity	0.175-0.250 kg/m ² , contingent upon the type of surface

The information presented in this technical data sheet is derived from data collected during testing. The user assumes full responsibility for the proper use of our original product. Our company is exclusively accountable for the product's quality. This data sheet supersedes the information found in the prior data sheet. Our company retains the right to modify any information included in this data sheet.



Advantages

This road marking paint, intended for use on asphalt, roads, parking lots, and various surfaces, is distinguished by its exceptional wear resistance and a quick-drying, durable formulation. It effectively penetrates the substrate, ensuring reliable adhesion. Its application is straightforward, and due to its high mechanical strength, it creates a robust, long-lasting film on the surface.



Preparing the foundation

The surface to which the product is applied must be entirely dry, degreased, and free of contaminants.



Mixture

For the application of road marking solvent and/or cellulose solvent: dilute to 10-15%.



About the Application

Road marking paint, appropriately diluted if necessary, is applied to the cleaned surface utilizing a roller and/or an air or airless spray gun.



Consumption

It depends on the surface of application.



PACKAGE

A can with a weight of 20 kg



Shelf life

In unopened packaging, it can be stored for 12 months in a cool, dry location shielded from sunlight at a temperature ranging from +10°C to +25°C.



Attention

Avoid application in environments where ambient temperatures fall below 5°C or exceed 30°C. Refrain from applying in direct sunlight, rain, or windy conditions. Do not apply to surfaces that have been subjected to prolonged sunlight exposure, nor to frozen surfaces or those at risk of freezing within 24 hours.

R10: Keep away from children.

R20/22: Harmful if inhaled or ingested.

R52/53: Toxic to aquatic life, may result in long-term detrimental effects in the aquatic ecosystem.

R65: Harmful. May result in lung damage if ingested.

S7: Store in a tightly sealed container.

S24/25: Avoid contact with eyes and skin. S28: In the event of skin contact, rinse immediately with abundant water.

S29: Do not discharge into drains.

S46: If ingested, seek medical attention promptly and present this container or label.